

# Xerox® VersaLink® C8000W Color Printer



The VersaLink® C8000W Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to [www.xerox.com/C8000W](http://www.xerox.com/C8000W)

SYSTEM SPECIFICATIONS	VERSALINK® C8000W/DT
<b>One-Sided Speed<sup>1</sup></b> 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm
<b>Two-Sided Speed<sup>1</sup></b> 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 205,000 pages/month
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 20,000 pages per month
<b>Hard Drive</b>	320 GB HDD (Optional)
<b>Processor</b>	1.6 GHz Dual-Core
<b>Memory</b>	4 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

DEVICE SPECIFICATIONS				
<b>ELECTRICAL REQUIREMENTS</b>				
North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240V +/- 10% Frequency: 50/60 Hz +/-3%, 10A			
<b>POWER CONSUMPTION</b>				
Printing <sup>4</sup>	For 110V: 2.30 kWh For 220V: 2.32 kWh			
Standby Mode <sup>4</sup>	110V: 75.3 Watts or less 220V: 73.8 Watts or less			
Sleep Mode <sup>4</sup>	110V: 0.48 watts or less 220V: 0.53 watts or less			
<b>OPERATING ENVIRONMENT</b>				
Required Temperature Range (Storage)	Below 48° C, and in compliance with MN2-810.13			
Required Temperature Range (Operating)	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85%			
Required Relative Humidity	15% to 85% Must be 62.5% or below at 32° C			
Sound Power Levels	Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less  Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A)			
Sound Pressure Levels	Printing: 56.8 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 10 seconds (without HDD) Less than 16 seconds (with HDD)			
<b>DIMENSIONS AND WEIGHT (UNPACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
VersaLink® C8000W/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb./80.8 kg
Two-Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb./27.2 kg
Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb./33.8 kg
High Capacity Feeder	15.3 in./389 mm	23.7 in./602.9 mm	15.0 in./380.01 mm	63.9 lb./29.0 kg
Office Finisher	19.7 in./501 mm	25.7 in./653 mm	38.7 in./983 mm	55.1 lb./25 kg
Booklet Maker Option for Office Finisher	11.75 in./298.5 mm	26.4 in./673 mm	42.5 in./1080 mm	22.0 lb./10 kg
BR Booklet Maker Finisher	30.28 in./769.2 mm	28.5 in./723 mm	41.5 in./1055.1 mm	134.3 lb./60.9 kg

# Xerox® VersaLink® C8000W Color Printer

<b>DIMENSIONS AND WEIGHT (PACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
VersaLink® C8000W/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb./95 kg
High Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb./33.7 kg
Two-Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb./33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb./39 kg
Office Finisher	31.1 in./790 mm	38.9 in./990 mm	21.8 in./555 mm	77.1 lb./35 kg
Booklet Maker Option for Office Finisher	19.4 in./495 mm	30 in./761 mm	16.9 in./430 mm	31 lb./14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb./77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb./6.5 kg

## CERTIFICATIONS

To view the latest list of certifications, go to [www.xerox.com/OfficeCertifications](http://www.xerox.com/OfficeCertifications).

## PRINT

<b>First-Print-Out Time</b>	As fast as 15 seconds color As fast as 14 seconds White
<b>Print Resolution</b>	Up to 1200 x 2400 dpi
<b>Page Description Languages</b>	Adobe® PostScript® 3™
<b>Color Management</b>	Xerox Color Management for 12 different media colors
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from side and trail edges of paper
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Banner Pages Enable/Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Finishing (requires finishing)</li> <li>Fit to New Paper Size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable/Disable</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming: covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Xerox® Earth Smart Driver Settings</li> </ul>
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>Windows® 7, 8, 8.1, 10</li> <li>Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019</li> <li>macOS® 10.14, 10.15, 11</li> </ul> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>.</p>

# Xerox® VersaLink® C8000W Color Printer

<b>Fonts</b>	PostScript fonts: 136
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
<b>SECURITY</b>	
<b>Security Features</b>	<p>Access Controls            AES 256-bit Encryption            Audit Log            Certificate Path Validation            Certificate Revocation List (CRL)/Status Protocol (OCSP)            Detection of external program falsification (XCP Plug-in)            Cisco® Identity Services Engine (ISE) Integration            Domain Filtering            FIPS 140-2            Firmware Verification            Immediate Disk Overwrite*            IP Address Filtering            IPsec            Network Authentication            Port Filtering            Pre-installed Self-Signed Certificates            Role Based Permissions            Secure Print            Security Certificate Management            SNMPv3            Status Protocol (OCSP)            TLS/SSL            Trusted Platform Module (TPM)</p> <p>*Requires HDD/Productivity Kit</p>
<b>ACCOUNTING</b>	
<b>XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)</b>	
<b>Tracking</b>	Print usage
<b>Accounting</b>	<p>Xerox® Standard Accounting Tool            Up to 1,000 User Accounts without HDD            Up to 9,999 User Accounts with HDD            Up to 500 General accounts</p> <p>Network Accounting (Job Based Accounting)            Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD            Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD            Up to 14,000 accounting records (transactions)</p>
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
<b>ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)</b>	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>• Comprehensive management and enterprise-scale tracking and reporting of device print usage</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>• Device requests account authentication from third-party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third-party Networking Account</li> </ul>

<b>PAPER HANDLING</b>			
<b>BYPASS TRAY</b>			
<b>Capacity<sup>5</sup></b>	100 sheets		
<b>Sizes</b>	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm		
<b>Weights</b>	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled
<b>TRAY 1 AND 2</b>			
<b>Capacity<sup>5</sup></b>	520 sheets each		
<b>Sizes</b>	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
<b>Weights</b>	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-printed Recycled
<b>TWO-TRAY MODULE</b>			
<b>Capacity<sup>5</sup></b>	1,040 sheets		
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
<b>Weights</b>	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled

<b>TANDEM TRAY MODULE</b>																
<b>Capacity<sup>5</sup></b>	2,000 sheets															
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5															
<b>Weights</b>	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm															
<b>Types</b>	<table border="0"> <tr> <td>Bond</td> <td>Hole Punched</td> <td>Lightweight Cardstock</td> </tr> <tr> <td>Plain Paper</td> <td>Labels</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Cardstock</td> <td>Heavyweight Cardstock</td> <td>Pre-Printed</td> </tr> <tr> <td>Custom</td> <td>Heavyweight Glossy Cardstock</td> <td>Recycled</td> </tr> <tr> <td>Glossy Cardstock</td> <td>Letterhead</td> <td></td> </tr> </table>	Bond	Hole Punched	Lightweight Cardstock	Plain Paper	Labels	Lightweight Glossy Cardstock	Cardstock	Heavyweight Cardstock	Pre-Printed	Custom	Heavyweight Glossy Cardstock	Recycled	Glossy Cardstock	Letterhead	
Bond	Hole Punched	Lightweight Cardstock														
Plain Paper	Labels	Lightweight Glossy Cardstock														
Cardstock	Heavyweight Cardstock	Pre-Printed														
Custom	Heavyweight Glossy Cardstock	Recycled														
Glossy Cardstock	Letterhead															
<b>HIGH CAPACITY FEEDER</b>																
<b>Capacity<sup>5</sup></b>	2,000 sheets															
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5															
<b>Weights</b>	18 lb. bond to 95 lb. cover/64 to 216 gsm															
<b>Types</b>	<table border="0"> <tr> <td>Bond</td> <td>Glossy Cardstock</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Plain Paper</td> <td>Hole Punched</td> <td>Recycled</td> </tr> <tr> <td>Cardstock</td> <td>Letterhead</td> <td></td> </tr> <tr> <td>Custom</td> <td>Lightweight Cardstock</td> <td></td> </tr> </table>	Bond	Glossy Cardstock	Lightweight Glossy Cardstock	Plain Paper	Hole Punched	Recycled	Cardstock	Letterhead		Custom	Lightweight Cardstock				
Bond	Glossy Cardstock	Lightweight Glossy Cardstock														
Plain Paper	Hole Punched	Recycled														
Cardstock	Letterhead															
Custom	Lightweight Cardstock															
<b>ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)</b>																
<b>Capacity<sup>5</sup></b>	Up to 50 envelopes															
<b>Sizes</b>	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm															
<b>TOTAL CAPACITY</b>																
<b>VersaLink® C8000/DT/W</b>	1,140 sheets															
<b>Maximum Capacity<sup>5</sup></b>	5,140 sheets															
<b>FINISHING</b>																
<b>OUTPUT TRAYS</b>																
<b>Dual Offset Catch Tray</b> (Standard when finishers are not attached)	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)															
<b>OFFICE FINISHER (OPTIONAL)</b>																
<b>Capacity<sup>5</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) Offset available for collated sets of standard size paper (8.5 x 11 in./A4 to 11 x 17 in./A3)															
<b>Sizes</b>	11.7 x 17 in./297 x 432 mm minimum for stapling 210 x 148 mm															
<b>Weights</b>	18 lb. bond/60 to 256 gsm															
<b>Multi-position Stapling</b>	50 sheets of 24 lb. bond/90 gsm															
<b>Hole Punch (Optional)</b> North America: Europe and Other Geographies:	Up to 65 lb. cover (220 gsm uncoated) 2/3 hole punch 2/4 hole punch															
<b>BOOKLET MAKER FOR OFFICE FINISHER (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)</b>																
<b>Capacity<sup>5</sup></b>	40 booklets (2 to 15 sheets per booklet – 20 lb./80 gsm or less)															
<b>Sizes</b>	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF															

# Xerox® VersaLink® C8000W Color Printer

<b>Saddle-stitch Stapling</b>	2 to 15 sheets/8-60 page booklet 18 lb. bond to 24 lb. bond/60 to 90 gsm (up to 220 gsm can be used for cover only)
<b>Score/Crease</b>	1 to 15 sheets/unstapled/60 to 105 gsm only
<b>OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)</b>	
<b>Capacity<sup>5</sup></b>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
<b>Sizes</b>	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
<b>Weights</b>	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
<b>Hole Punch</b> North America Europe	2/3 hole punch 2/4 hole punch 4 hole “Swedish” punch (optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
<b>DEVICE MANAGEMENT</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>REMOTE CONTROL PANEL</b>	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
<b>XEROX® CENTREWARE® WEB</b>	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device

# Xerox® VersaLink® C8000W Color Printer

<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
<b>REMOTE SERVICES</b>		
<b>Xerox® Automated Meter Reads (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
<b>WHAT'S IN THE BOX</b>		
	<ul style="list-style-type: none"> <li>• VersaLink® C8000W/DT Color Printer</li> <li>• Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 8,000 print capacity<sup>6</sup>, White: 5,000 print capacity)</li> <li>• Drum Cartridge – One of each (Cyan, Magenta, Yellow, &amp; White: 240,000 print capacity)<sup>7</sup></li> <li>• Quick User Guide</li> <li>• Install Guide</li> <li>• Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide)</li> <li>• Power Cord</li> </ul>	
<b>SUPPLIES AND ACCESSORIES</b>	<b>QUANTITY</b>	<b>PART NUMBER</b>
<b>SUPPLIES</b>		
<b>Standard Capacity Toner Cartridges</b>	Cyan: 7,600 standard pages <sup>6</sup> Magenta: 7,600 standard pages <sup>6</sup> Yellow: 7,600 standard pages <sup>6</sup> White: 5,000 standard pages <sup>8</sup>	106R04042 106R04043 106R04044 106R04646
<b>High Capacity Toner Cartridges</b>	Cyan: 16,500 standard pages <sup>6</sup> Magenta: 16,500 standard pages <sup>6</sup> Yellow: 16,500 standard pages <sup>6</sup>	106R04054 106R04055 106R04056
<b>Drum Cartridge</b>	Cyan: 210,000 standard pages <sup>7</sup> Magenta: 210,000 standard pages <sup>7</sup> Yellow: 210,000 standard pages <sup>7</sup> White: 240,000 standard pages <sup>7</sup>	101R00602
<b>Waste Cartridge</b>	30,400 standard pages <sup>7</sup>	108R01504
<b>IBT Cleaner</b>	160,000 standard pages <sup>7</sup>	104R00256
<b>Transfer Roller</b>	200,000 standard pages <sup>7</sup>	116R00015
<b>Office Finisher Booklet Maker Cartridge (8 cartridges per container)</b>	16,000 staples (2,000 each cartridge)	008R12897
<b>Staple Refills for Office Finisher (3 refills per container)</b>	15,000 staples (5,000 each refill)	008R12941
<b>Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)</b>	5,000 staples (5,000 each cartridge)	008R12964
<b>Staple Cartridges for BR Booklet Maker (1 cartridge per carton)</b>	5,000 staples (5,000 each cartridge)	008R13177



# Xerox® VersaLink® C8000W Color Printer

<b>ACCESSORIES/OPTIONS</b>	
<b>Two-Tray Module</b>	097S04969
<b>Tandem Tray Module</b>	097S04970
<b>High Capacity Feeder</b>	097S04845
<b>Envelope Tray (Replaces Tray 1)</b>	497K17880
<b>Office Finisher</b>	097S05019
<b>2/3 Hole Punch for Office Finisher (available in Eastern Hemisphere)</b>	497K20600
<b>2/4 Hole Punch for Office Finisher (available in Western Hemisphere)</b>	497K20610
<b>Booklet Maker for Office Finisher</b>	497K20590
<b>BR Booklet Maker Finisher with 2/3 Hole Punch (requires Horizontal Transport Kit)</b>	097S04981
<b>BR Booklet Maker finisher with 2/4 Hole Punch (requires Horizontal Transport Kit)</b>	097S04982
<b>Horizontal Transport Kit for BR Finisher</b>	497K17440
<b>320 GB HDD</b>	097S04971
<b>Wireless Network Adapter Kit</b>	497K16750
<b>Internal Card Reader/RFID Kit</b>	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)
<b>Bianco Digitale SW Kit</b>	497N07139

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

<sup>8</sup> Using 5% coverage.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.